



Audio

Frequency response

35Hz - 180Hz (typical in-room)

Speaker units

170mm Ruark long-throw subwoofer
170mm Ruark passive radiator

Amplifier

100W nominal Class D

Enhancements

Auto-standby and wake-up
180 degree phase switch
Adjustable crossover (50-180Hz)
Adjustable level control
Soft clip protection filter

Cabinet type

Tuned passive radiator

Cabinet volume

9.5 Litres

Tuning frequency

45Hz

Connectivity

Sub in-put

Mono RCA input (up to 2.3 Vrms)

General specifications

Standard finishes

Charcoal Lacquer panels with Dark Slate fabric grille
Rich Walnut panels with Dark Slate fabric grille

Product dimensions (cabinet)

H270 x W250 x D250mm

Product Dimensions (max)

(Inc feet, controls & cables)
H300 x W250 x D285mm

Product weight

6.7kg

Gift carton dimensions

H400 x W350 x D350mm

Packaged weight

8.3kg

Product power input

90-240VAC 50-60Hz 2.5A
IEC C8 figure of 8 socket

Power consumption

0.5W standby
7W typical

In the box

RS1 Subwoofer
2m AC power cable
3m RCA subwoofer cable
Quick start guide



Rich
Walnut



Charcoal
Lacquer